

FOBRO Oscillator side harvester



FOBRO Oscillator, the side rover for high row crops. Built for the toughest conditions, this rig has proven its worth in daily use in large and small tree nurseries for more than 10 years. Bare roots such as e.g. Avenue trees, deciduous trees, softwoods, shrubs, roses, fruit trees and many more are carefully dug with a minimum of energy.



Standard equipment

In the direction of travel before and cut back the grubber blade

Your advantage

The grubber blade, which cuts through the ground, requires minimal pulling power. The side pull of the tractor is considerably lower. The swinging grubber blade does not scrape the soil and compact it as it does with a stiff grubber blade. As a result, they harvest more of the root system.

More root system = better quality = satisfied customers = better prices = More profit!

Vibrating sieve integrated in the hatchet

Guarantees a gentle sifting of the soil and lift the lances out of the ground without moving them.

Adjustable shaking motion

In very wet and heavy soil performs a stronger strike; better separation of the soaked ground.

Side and in depth adjustable counterbalance / stabilizer

By optimal adjustment of the counter-train the directional stability is guaranteed.

Laterally adjustable grubber blade

The lateral adjustability makes it possible to match the working width exactly to the outside width of the tractor. This allows an often necessary use of wide tires or double wheels.

Three adjustable support wheels

A single and on the grubber side a double wheel guarantee an accurate depth control.

One big flywheel

The movements required for the optimal shaking action are intercepted, resulting in a smooth running.

Interchangeable wear gauge

Low maintenance costs

Additional equipment

Root undercutting blade

Your advantage

The unique movement of the blade in the direction of travel prevents the roots from being „attached“. This keeps the movement of the plants at the minimum.

Technical Data:

FOBRO Oscillator side grubber

Working width	The inner width is 55 cm
Working depth	Maximum 50 cm
Machine width	The width is adjustable from 3 m to 3,5 m (outer width)
Tractor track width	Is not important, max. Tractor outside width is 3 m
Passage	Unlimited, the plants are not run over
Weight	990 kg
Power requirements	Tractors with 2 wheel drive > 90 HP / Tractors with 4 wheel drive > 70 HP
PTO	540 or 1000 rpm, operating speed 400 540 rpm

Technical changes and product improvements reserved

Baertschi Agrartecnic Deutschland GmbH

D-88255 Baienfurt (Vertrieb, Ersatzteile EU)
T: +49 751 7687 0000 / F: +49 751 7684 472 / info@baertschi.com

Baertschi Fobro INC LLC

Grand Haven, Michigan, 1715 Airpark Dr Grand Haven
(Import USA) M: 49 417 94 24 / usa@baertschi.com

Baertschi - Fobro d.o.o.

BiH-74250 Maglaj (Produktion, Vertrieb Balkan)
M: +387 61 050 908 / F: +387 61 684 21 768

Baertschi Agrartecnic AG

Hauptsitz
Bruggmatte 11, CH-6262 Langnau b.R.
(Service, Ersatzteile, Verkauf CH)
T/F: +41 41 989 81 10 / info@baertschi.com

Dealer: